## 2.0KG ABE DRY CHEMICAL POWDER FIRE EXTINGUISHER





## **SPECIFICATIONS**

PRODUCT CODE	FXM20
CAPACITY	2.0 kg
FIRE RATING	2A:30B:E
AGENT	90% MAP Dry Chemical
	Powder
OPERATING PRESSURE	1000 kPa
DISCHARGE TIME	14 seconds
PRODUCT DIMENSIONS	390 mm X 120 mm
(H X CYL Ø)	
CYLINDER THICKNESS	1.0 mm
OVERALL MASS	3.4 kg
O 7 210 (22 10) (30	
CYLINDER	Steel, UV Powder Coat
CYLINDER	Steel, UV Powder Coat
CYLINDER HANDLE	Steel, UV Powder Coat Stainless Steel
CYLINDER HANDLE VALVE	Steel, UV Powder Coat Stainless Steel Chrome plated Brass
CYLINDER HANDLE VALVE HOSE	Steel, UV Powder Coat Stainless Steel Chrome plated Brass EPDM, Brass ferrules
CYLINDER HANDLE VALVE HOSE APPROVALS	Steel, UV Powder Coat Stainless Steel Chrome plated Brass EPDM, Brass ferrules AS/NZS 1841.5
CYLINDER HANDLE VALVE HOSE APPROVALS SHIPPING DIMENSIONS	Steel, UV Powder Coat Stainless Steel Chrome plated Brass EPDM, Brass ferrules AS/NZS 1841.5 410 mm X 150 mm X 130









## **APPLICATION**

- Suitable for A Class Fires (paper, wood, textiles)
- Suitable for B Class Fires (flammable liquid fires such as oils, paints and solvents)
- Suitable for E Class Fires (energised electrical fires such as switch boards and electrical motors)

