

axis

JS7000K

7" MONITOR & CAMERA KIT

A universal monitor & camera system for in-vehicle reversing applications. Suitable for most vehicles, trucks and caravans. The weatherproof camera offers a clear image and enhanced view when reversing.

- Complete Reversing Solution
- Selectable Normal/Mirror Image
- Selectable Guidelines



12-24  VOLT



7^{inch} LCD



axis



JS7000K 7" MONITOR & CAMERA KIT

SPECIFICATIONS

JS7000 MONITOR

- TFT Panel: New Grade A LCD
- LCD Size: 178mm (7-Inch) Diagonal
- Display Format: 16:9
- Resolution: 800 x 480
- Brightness: < 500 CD/M2
- Viewing Angles: 70° Left/Right/Up/Down
- Video System: Auto PAL/NTSC Select
- Video Connect: 2 x 4-Pin (Female)
- Reverse Trigger: Camera 2 Only
- Monitor View: Normal/Mirror Image Select
- Buttons: Illuminated
- Guidelines: Selectable On/Off (Camera 2 Only)
- Audio: On Board Speaker
- Menu: OSD
- Main Menu: Brightness/Contrast/Colour/Volume/Guidelines (On/Off)/Reset/Language
- Operating Temp: -20°C to +70°C
- Power Input: 10-32V DC (Negative Ground)
- Dimensions: 180W x 122H x 28D mm (excluding bracket)
- Finish: Matt Black Rubber, Matt Metal

CAMERA

- Image Sensor: 1/3" Sony CCD
- Auto Lens: f2.9mm
- Electronic Shutter: Auto
- Vertical Viewing Angle: 120°
- Horizontal Viewing Angle: 90°
- Signal System: PAL
- Resolution: 700 TV Lines
- Sync System: Internal
- Orientation: Mirror Image
- Night Vision: Yes, 18 LED
- Illumination: 0 Lux with IR on
- Ingress Protection: IP67
- Operating Temperature: -20°C ~ 70°C
- Dimensions: 70W x 45H x 60D mm (Excl Bracket)
- Connection: Terminated 4-Pin Male
- Power Supply: 12V DC (From Monitor)

**Glass Mount Bracket
(BKT101) Also Available**



INCLUDED IN THE BOX



JS7000 Monitor

U-Shape Mount




Remote Control



Power Cable Assembly



Sunshade



Camera

15m 4 Pin (Male) to 4 Pin (Female) Extension Cable



Mounting Bracket



Sunvisor



9 321886 014273



Due to improvements in technology and design, specifications are subject to change without notice.
Made in China