




NEW RELEASE



- All-in-one 5 function design
- Second generation with retro reflector
- Grilamid® Lens (high performance polyamide)
- HCS Technology (12V and 24V)
- Lifetime Warranty*
- Suitable for trucks, utes and trailers



DT version



All dimensions in mm







4963-P 6 pole DT plug, wedge and 6 contacts (DT version) (not included with lamp)

HELLA DuraLED® Combi-SR with Retro Reflector Lamp Functions





Rear position Stop





HELLA Australia: 1800 061 729

Rear direction indicator

Reverse

HELLA DURALED® COMBI-SR

Stop/Rear Position/Rear Direction Indicator/Reversing Lamp with Retro Reflector

The new all-in-one five function HELLA DuraLED® Combi-SR Lamp now incorporates a built-in retro reflector, saving both time and money on installation. The all-in-one design makes the DuraLED® Combi-SR the ideal choice for vehicles with limited space to mount a separate reflector.

DT Connector options enhance installation flexibility and the innovative HCS feature means these lamps work seamlessly with many late model vehicle electrical systems. Made with a high performance $\operatorname{Grilamid}^*$ lens offering unmatched resistance to impact, long term UV exposure and commonly used chemicals.

As with all products in the DuraLED® range, this new lamp offers superior durability and a class leading lifetime warranty* for complete peace of mind.















Part Number	Description	Packaging
2VP 015 074-001	2.5m cable version	CARTON PACK
2VP 015 074-002	2.5m cable version	BLISTER PACK
2VP 015 074-007	2.5m cable version	PACK OF 12
2VP 015 074-101	2.5m cable version with HCS Technology	CARTON PACK
2VP 015 075-001	DT version	CARTON PACK
2VP 015 075-101	DT version with HCS Technology	CARTON PACK
Mounting	Suitable for horizontal mounting Two hole surface mount with mounting bushes supplied	
Voltage	Multivolt™ suitable for 12 and 24 volt systems	
Power Consumption	Stop: 5W Rear position: 1.5W Rear direction indicator: 6W Reverse: 2W Night light: 1.5W (DT ver	rsion only)
Protection	Reverse polarity and 5000 watt Transient Voltage Suppressor (TVS) IP 6K7 (Protection against dust and temporary water immersion) IP 6K9K (Protection against dust and high-pressure/steam jet cleaning)	
Cable Length	Pre-wired with 2.5m of sheathed multi-core cable (non DT version)	
Accessory	4963-P 6 pole DT plug, wedge and 6 contacts (DT version) (not included with lamp)	
Lens Material	Grilamid*	
Compliance	ECE R148 ECE R150 ECE R10 ISO 1	3207-1

HCS Technology - HELLA Compatibility Solution These lamps are designed to International Standard ISO 13207-1 to provide compatibility with commercial vehicle indicator failure systems. *Lifetime means the economic life of the vehicle these products were first installed on.